
# TTANIUM



## TITANIUM Planter suitable for No-Till and Conventional Tillage



# The TITANIUM mechanical seed meter

# The APOLLO RAMPFLOW seed discs and runners.



## **SEED HOPPER**

35 Litre capacity

### **WEIGHT DISTRIBUTOR**

Allows only the right amount of seed to be on top of the seed disc independent of the volume in the seed hopper.

#### **INSPECTION WINDOW**

#### **FLEXIBLE SEED ORGANIZERS**

## **FLEXBRUSH ROLLER**

One universal roller for almost all crops ejects seeds from the seed disc that would not fall out by gravity alone.

## **ANTIBOUNCE BRUSH**

Keeps the seed in the place during the last rotational stage.

## APOLLO RAMPFLOW SEED DISC

Skips and doubles are almost eliminated by the shallower side wall to the rear side of each seed hole.

## **APOLLO DISC RUNNER**

Between two and five different runners are available depending on the planted crop. Some have a deeper and some a shallower surface to accommodate a wide variety of seed shapes and sizes.



The TITANIUM seed meter gives the user peace of mind during the planting process.

### **INSPECTION WINDOW**

It allows the user to check the seed meter's performance during planting. A possibility for skips and doubled is greatly eliminated with the correct choice of seed disc and disc runner and the inspection window makes it possible for the user to double check whether the right choice was made. There should be no skips or double seeds in the seed disc as it rotates over the drop out hole. This and the proper exit of the seed from the seed disc can easily be observed through the window.



#### **FLEXIBLE SEED ORGANIZERS**

Three polyurethane ORGANIZERS ( see 1, 2 & 3 ) are positioned at different angles against the running direction of the seed disc ( red arrow ). These ORGANIZERS wipe the seeds gently into the seed disc ensuring each hole in the seed disc is filled with only one seed at a time. The flexibility of the ORGANIZERS prevent seed from being damaged during the organising process.

## TOP PERFORMANCE IS GUARANTEED BY USING



## Fertiliser Auger

## Wheel and Tool Options



· Self-cleaning auger


High and low output

Easy to exchange


available.

- Replaceable Polyacetal moulded lining
- Great durability
- · Low friction with fertiliser
- Overflow for when fertiliser opener is blocked
- Rain cap can be taken off to monitor flow
  - Corkscrew design prevents fertiliser build-up around the auger, even when fertiliser quality is poor.

## **Reliable Flow rate:**







- Double sealed ball bearings
- Special grease ensures low torque and high durability
- · Five fold protection between bearing and fertiliser
- Self cleaning discharge hole








TITANIUM TITANIUN **Covering Blades** 

**Notched Boron Steel Wheels** (standard)



(standard)

(optional)



**Covering Discs** (optional)

## TITANIUM

## Mechanical Planter Precision Planting on a Budget

