



RENOVATOR CLASSIC



PROVEN 25mm COIL TINES



Agitator shaft to help prevent seed compaction



Weigh kit including scales comes as standard



Easy calibration system with simple seed diversion into the trays provided




25mm coil tines for superior strength and consistent seeding



Built to Duncan's high standard



Large and small metering wheels for sowing a wide range of products from turnips through to peas and fertiliser



FARMER'S DRILL PROVEN MUSCLE



A positive drive via an adjustable ground driven jockey wheel



Duncan 'T' boots have extra strength with Ni-hard steel and a tungsten tile on the leading edge



Easy to set depth adjustment with a collar and threaded shaft adjuster



Individually sprung disc openers with easy change discs, seals and bearings are available as an option



Optional following tools: Uni-Roller and/or Tine Harrows



Easy access to rear platform is standard



FEATURES

RENOVATOR CLASSIC

Standard features

- 6 inch row spacing
- 25mm coil tine and Duncan 'T' boot with tungsten tile on leading edge
- Weigh kit with scales
- Safety chains
- Stainless steel agitator shaft
- Peg roller seeder unit

Options and accessories

- Disc openers on the front of the drill
- Tine Harrow or Uni-Roller following tool
- Rear tow bar
- Stainless steel box(es)
- Seed level indicator
- Hydraulic cylinder for drawbar
- Hydraulic cylinder for disc openers
- Baffle extension kit
- Lighting kit
- Harrow transport kit
- Jack stand
- Weather skirts to cover over seeder units

DIMENSIONS & CAPACITIES

| 19 ROW / 3 METRE | |
|---|-------|
| Width (Over Wheels) (mm) | 3026 |
| Height (Ground Wheels Up) (mm) | 1700 |
| Overall Length (mm) | 3512 |
| Weight Inc. Disc Openers (Unladen) (kg) | 1610 |
| Row Spacing (mm) | 147.5 |
| Effective Sowing Width (mm) | 2800 |
| Box Capacity (Lt Per Box) | 348 |



DUNCAN AG NEW ZEALAND

PO BOX 2018,
WASHDYKE 7941, TIMARU
PH: 0800 177 171
Email: admin@duncanag.co.nz
www.duncanag.com

DUNCAN AG AUSTRALIA

4B SILVERTON CLOSE,
NORTH LAVERTON, VICTORIA 3026
PH: 03 9314 9666
Email: admin@duncanag.com.au

In accordance with the company's policy of continuous improvement to its machines, alterations in specifications may be made without notice. The company accepts no responsibility for any discrepancies which may occur between specifications of its machines and the descriptions thereof contained in this publication.

